List of Figures

Figure 1.1: Green-band 3

Figure 1.2: Isochronet switch organization 12

Figure 1.3: Mean frame delay comparison (in μs) for Poisson arrivals and deterministic service (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 17

Figure 2.1: Store-and-forward routing on trees 23

Figure 2.2: Circuit motion on trees 27

Figure 2.3: Characteristics of proposed high-speed architectures 38

Figure 3.1: Green-band 42

Figure 3.2: Example network topology 43

Figure 3.3: Example routing tree allocation 43

Figure 3.4: Example band allocation 44

Figure 3.5: Control of contention through degree of band overlap 44

Figure 3.6: Multiple non-interfering trees 46

Figure 3.7: Multiple protocol stacks in Isochronets 48

Figure 4.1: Example network topology 60

Figure 4.2: Band and overlap constraints 63

Figure 5.1. Synchronous Protocol Stack (SPS) structure 80

Figure 5.2. Handling signals in the protocol stack 82

Figure 5.3. LTM-MAC SAPs 83

Figure 5.4. Isochronous transmissions 89

Figure 6.1: Tree allocation and node configuration 106

Figure 6.2: Configuration Table structure 107

Figure 6.3: Configuration Table in a particular network node.....108

Figure 6.4: Switch organization.....110

Figure 6.5: Input Card.....111

Figure 6.6: Switching Fabric.....112

Figure 6.7: Control Unit.....113

Figure 6.8: Configuration Memory 114

Figure 6.9: Output Card 116

Figure 6.10: Isoswitch implementation 117

Figure 6.11: Isochronet interface to an end machine 119

Figure 6.12: Interconnection between the Isoswitch and the Host machine 119

Figure 6.13: WDM allocation to routing trees 126

Figure 6.14: All-optical switch implementation: one tree per band 126

Figure 6.15: Selection box.....127

Figure 7.1: Contention for an outgoing link in RDMA 136

Figure 7.2: RDMA- model 138

Figure 7.3: RDMA++ model 143

Figure 7.4: Residual service time 145

Figure 7.5: Residual vacation time.....146

Figure 7.6: RDMA+ model 148

Figure 7.7: Mean frame delay (in μs) for Poisson arrivals and deterministic service under RDMA++ (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 152

Figure 7.8: Mean frame delay (in μs) for Poisson arrivals and Poisson service under RDMA++ (the mean frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 152

Figure 7.9: Mean frame delay (in μs) for Poisson arrivals and Poisson service under RDMA++ (the mean frame size is 530 bytes, the link speed 24 Gb/s, the band size 25 μs, the cycle period 125 μs) 153

Figure 7.10: Mean frame delay (in μs) for Poisson arrivals and deterministic service under RDMA++ (the frame size is 530 bytes, the link speed 24 Gb/s, the band size 100 μs, the cycle period 125 μs) 153

Figure 7.11: Mean frame delay (in μs) for Poisson arrivals and deterministic service under CS (the frame size is 53 bytes, the link speed 2.4 Gb/s, the circuit size 2.5 μs, the cycle period 125 μs) 155

Figure 7.12: Mean loss rate for Poisson arrivals and deterministic service under RDMA- (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 155

Figure 7.13: Mean frame delay (in μs) for Poisson arrivals and deterministic service under RDMA+ (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 156

Figure 7.14: Mean frame delay comparison (in μs) for Poisson arrivals and deterministic service (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 25 μs, the cycle period 125 μs) 158
Figure 7.15: Mean frame delay comparison (in μs) for Poisson arrivals and Poisson service (the frame size is 530 bytes, the link speed 24 Gb/s, the band size 25 μs, the cycle period 125 μs) 158
Figure 7.16: Simulated network topology 160
Figure 7.17: Allocation of trees in one band.....160
Figure 7.18: Mean frame delay comparison (in μs) for Poisson arrivals and deterministic service (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 41.67 μs, the cycle period 125 μs) 162
Figure 7.19: Mean frame delay comparison (in μs) for Poisson arrivals and Poisson service (the frame size is 530 bytes, the link speed 2.4 Gb/s, the band size 41.67 μs, the cycle period 125 μs) 163
Figure 7.20: Mean frame delay comparison (in μs) for Poisson and deterministic arrivals and deterministic service under RDMA++ (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 41.67 μs, the cycle period 125 μs) 164
Figure 7.21: Mean frame delay (in μs) for Poisson arrivals and deterministic service under RDMA++ (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 41.67 μs, the cycle period 125 μs) 164

Figure 7.22: Mean loss rate for Poisson arrivals and deterministic service under RDMA- (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 41.67 μs, the cycle period 125 μs) 165

Figure 7.23: Mean frame delay comparison (in μs) for Poisson arrivals and deterministic service (the frame size is 53 bytes, the link speed 2.4 Gb/s, the band size 17.8571 μs, the cycle period 125 μs) 166

Figure 8.1: Two level hierarchical clustering of Isochronets 170

Figure 8.2: Two non interfering routing trees to a single destination 172