

## Requirements for Session Initiation Protocol (SIP)-based Emergency Calls

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of Section 10 of RFC2026.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as “work in progress.”

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>

To view the list Internet-Draft Shadow Directories, see <http://www.ietf.org/shadow.html>.

### Copyright Notice

Copyright (c) The Internet Society (2003). All Rights Reserved.

### Abstract

This document enumerates requirements for emergency calls in VoIP and general Internet multimedia systems. We divide the requirements into “last-mile” and “end-to-end”. Last-mile solutions only exchange the emergency call center’s circuit-switched access by an IP-based system. The requirements for end-to-end IP-based emergency calling address functional and security issues for determining the correct emergency address, for identifying the appropriate emergency call center and for identifying the caller and its location. While we focus on systems that employ the Session Initiation Protocol (SIP), many of the requirements may also apply to other environments, such as those using H.248/Megaco, MGCP or H.323.

## Contents

<b>1</b>	<b>Conventions used in this document</b>	<b>2</b>
<b>2</b>	<b>Introduction</b>	<b>2</b>
<b>3</b>	<b>Definitions</b>	<b>3</b>
<b>4</b>	<b>Last-Mile Access</b>	<b>3</b>
<b>5</b>	<b>End-to-End IP-Based Emergency Calls</b>	<b>6</b>
5.1	Emergency Address . . . . .	6
5.2	Identifying the Appropriate Emergency Call Center . . . . .	7
5.3	Identifying the Caller . . . . .	9
5.4	Identifying the Caller Location . . . . .	10
<b>6</b>	<b>Call Setup and Call Features</b>	<b>10</b>

<b>7 Security Considerations</b>	<b>11</b>
<b>8 References</b>	<b>11</b>
<b>9 Acknowledgments</b>	<b>12</b>
<b>10 Authors' Addresses</b>	<b>12</b>

## **1 Conventions used in this document**

The key words “MUST”, “MUST NOT”, “REQUIRED”, “SHALL”, “SHALL NOT”, “SHOULD”, “SHOULD NOT”, “RECOMMENDED”, “MAY”, and “OPTIONAL” in this document are to be interpreted as described in BCP 14, RFC 2119 [1].

## **2 Introduction**

Users of telephone-like services expect to be able to call for emergency help, such as police, the fire department or an ambulance, regardless of where they are, what (if any) service provider they are using and what kind of device they are using. Unfortunately, the mechanisms for emergency calls that have evolved in the public circuit-switched telephone network (PSTN) are not quite appropriate for evolving IP-based voice and real-time multimedia communications. This document outlines some of the requirements that end systems and network elements such as SIP proxies need to satisfy in order to provide emergency call services that offer at least the same functionality as existing PSTN services, while hopefully making emergency calling more robust, cheaper to implement and multimedia-capable.

In the future, users of other real-time and near real-time services may also expect to be able to summon emergency help. For example, instant messaging (IM) users may want to use such services. IM is particularly helpful for hearing-disabled users [4] and in cases where bandwidth is scarce. For lack of a better term, we will use the term “caller” or “emergency caller” to refer to the person placing an emergency call or sending an emergency IM.

Emergency callers and ECCs expect calls to be completed reliably. Where possible, a callback number and the current caller location should be delivered to the ECC to speed up emergency response and to limit prank calls.

The emergency calls described in this document differ from the emergency telecommunications service (ETS) described in [5]. In ETS, relatively small numbers of emergency workers need to maintain communication even when parts of the infrastructure are destroyed or disabled. Emergency calls, on the other hand, are placed by civilians to call for emergency services such as fire, ambulance and police services. Thus, these two services are complementary.

We distinguish two sets of requirements, one for last-mile use of SIP (Section 4), where VoIP emergency callers still use the existing PSTN, and end-to-end SIP emergency calls (Section 5) that terminate SIP-originated emergency calls without transitioning the PSTN.

There is a third approach, where SIP-originated calls terminate on a PSTN gateway in each emergency calling area. This architecture is left for future consideration.

### 3 Definitions

**Emergency call center (ECC):** An emergency call center (ECC) receives emergency calls within a specific geographic area and dispatches emergency services, such as fire, police and rescue services. An ECC may also serve as a backup for another ECC and, in backup mode, dispatch emergency services outside of its normal service region. In the United States and Canada, ECCs are called Public Safety Answering Points (PSAPs).

**Internet Protocol ECC (IECC):** An Internet protocol emergency call center (IECC) is an ECC that uses Internet protocols, such as SIP for call signaling, RTP for media delivery, to receive emergency calls.

**Call taker:** A call taker is an agent, typically a government employee, at the ECC that accepts calls and may dispatch emergency help. (Sometimes the functions of call taking and dispatching are handled by different groups of people, but these divisions of labor are not generally visible to the outside and thus do not concern us here.)

**Basic emergency service:** Basic emergency service allows a user to reach an ECC serving its current location, but the ECC may not be able to determine the identity or geographic location of the caller (except by having the call taker ask the caller).

**Enhanced emergency service:** Enhanced emergency services add the ability to identify the caller identity and/or caller location to basic emergency services. (Sometimes, only the caller location may be known, e.g., from a public access point that is not owned by an individual.)

**Last-mile emergency service:** In last-mile emergency service, the caller uses the existing PSTN infrastructure to place an emergency call. Only the path from the “selective router”, or the equivalent functionality outside North America, to the ECC uses IP-based communications. The call may well be placed from a VoIP device, but is assumed to enter the PSTN very close to the location of the caller. The use of Internet protocols is invisible to the caller.

**End-to-end emergency service:** In end-to-end emergency service, the caller and ECC both use Internet protocols end-to-end.

**Selective router:** A selective router or enhanced emergency call control office. The enhanced emergency call control office is “[t]he Central Office that provides the tandem switching of 9-1-1 calls. It controls delivery of the voice call with ANI to the PSAP and provides Selective Routing, Speed Calling, Selective Transfer, Fixed Transfer, and certain maintenance functions for each PSAP. Also known as 9-1-1 Selective Routing Tandem or Selective Router.” [?] The term may be specific to North America. [TBD: Find out if there are other terms.]

### 4 Last-Mile Access

In last-mile access, an ECC replaces an analog (CAMA) or digital (ISDN) trunk with packet-based access, typically over one or more high-speed access lines such as DSL or leased lines. The packet-based access terminates in the “selective router” that normally hands off calls to the ECC. Thus, the ECC becomes an IECC, but no larger scale infrastructure changes are required. To amplify, in the last-mile model, a SIP user agent calling for emergency assistance can NOT dial reach the ECC directly via a SIP session; rather, the

SIP session terminates on a PSTN gateway, traverses the PSTN as in today's circuit-switched environment and is only converted to VoIP at the selective router handling the ECC.

Last-mile access is motivated by cost and call setup considerations. It may be cheaper to use IP-based technology for the access link and ECC-internal communications. Also, many existing (US) PSAPs use analog technology (CAMA trunks), to receive emergency calls. These trunks, originally designed for operator positions, can pulse out the ten or 20-digit (for wireless) caller's number, but as dialed digits. Thus, they add several seconds of call setup delay. This can be particularly disconcerting since it affects the time until the call taker can pick up the call. IP-based communications, using, for example, SIP as a call signaling protocol, can effectively eliminate this extra caller identification delay. (Additional delays are caused by the often very low speed access to the mapping database that maps caller identity to geographic location.) Finally, since pending calls do not consume access network resources, such systems may be more robust in the face of overload.

- M1: Coexistence:** Due to the investment required, not all ECCs will convert to IP-based access at the same time. Thus, emergency calls **MUST** work in a network where some ECCs use existing (analog) technology, some ISDN, others IP. In particular, existing back-up relationships between ECCs must continue to work.
- M2: Call setup delay:** The call setup delay **MUST NOT** be no larger than for existing analog trunks and **SHOULD** be significantly smaller.
- M3: Call identification:** Signaling from the PSTN switch must be able to convey both ten and 20-digit caller identities (ANI – automatic number identification) used in North America and other digit strings used elsewhere.
- M4: Call transfer:** Call takers **MUST** be able to transfer active sessions to other call takers within the same ECC and to other ECCs, even those not using Internet.
- M5: Simultaneous alerting:** A given set of call takers must be alerted to any incoming emergency call.
- M6: Call routing:** The call may be awarded to the first call taker to answer or it may be routed to call agents based on policies, such as least-busy. Agents must be able to be assembled into multiple groups according to policies specified by ECC authorities. These groupings must be changeable by the ECC authority [2].
- M7: Call queuing:** It must be possible to queue calls, either in answered or unanswered state. Queued calls must be able to receive recorded announcements. ECC personnel, as directed by policy, should be able to modify the announcements. The call queue should allow automatic or manual transfer to another location of calls that exceed a particular expected waiting time [2].
- M8: Call identification:** The call taker **MUST** be able to distinguish the following incoming call types [2]:
- emergency calls dialed via a universal emergency number;
  - direct-dialed emergency calls;
  - transfers from other ECCs;
  - anonymous calls;
  - administrative calls;
  - call origination (wireline, wireless, TDD);

- default-routed calls (These are calls for which selective routing information was unavailable, resulting in the call being routed to a “default” ECC based on other criteria.)

**M9: Information delivery:** The call setup request **MUST** be able to deliver the following information [2]:

- called party number (to identify ECC or type of call);
- calling party number, including any numbering plan digits;
- delivery of indication of caller ID blocking for non-emergency calls;
- location information or lookup keys;
- ANI on abandoned calls;
- indication that a terminating emergency call has been alternate routed from another PSAP.

**M10: Agent sign-on:** Agents must be able to log on and log off; workstations conditions should at least include “ready”, “not ready” and “busy” [2].

**M11 Conferencing:** Occasionally, supervisors, translators or other specialists need to participate in an emergency call. Thus, it **MUST** be possible to add one or more parties, not necessarily located in the IECC, to any emergency call at any time.

**M12: Announcements:** Callers may receive automated announcements or other indications of call status [2].

**M13: Call queues:** Supervisors **MUST** be able to manage call queues.

**M14: Call metrics:** Supervisors and/or agents can measure call delays and other performance metrics [2].

**M15: Monitoring and recording:** In many jurisdictions, both sides of all emergency calls are automatically recorded as potential legal evidence. Thus, it **MUST** be possible to record and timestamp all signaling and media from all successful, queued, failed and aborted calls.

**M16: Abandoned calls:** ECCs need to be notified of abandoned calls, i.e., emergency calls that are dropped by the caller before being answered by a call taker.

**M17: Transition to end-to-end:** Protocols and architecture **SHOULD** be chosen so that a last-mile IECC can receive emergency calls placed by IP endpoints without major system changes or hardware upgrades.

**M18: Authentication of incoming calls:** The IECC **MUST** be able to ascertain that the calls it receives are indeed originating from the selective router.

**M19: Authentication of the IECC:** The selective router **MUST** be able to be assured that the calls it places reach the desired IECC rather than an impostor.

**M20: Confidentiality:** Implementations **MUST** support confidentiality for call signaling and media streams, to protect them against unauthorized disclosure to third parties.

**M21: Robustness:** An IECC **SHOULD** be able to automatically route all incoming calls to another backup IECC, even if the access link(s) to the primary IECC are inoperative. Any such redirection **MUST** be authenticated.

**M22: Overflow handling:** An IECC SHOULD be able to automatically route calls to another IECC if the (expected) waiting time exceeds a configured threshold.

**M23: Hold:** The call taker MUST be able to place the a call in a status that allows him/her to handle other calls without disconnecting from the caller. A visual/audible notification should be available for the call taker to alert them that a call is on hold. The call should continue to be recorded and an optional voice message should be made available for the caller so they are aware of the status of their call [2].

**M24: Forced disconnect of caller:** This will allow the ECC call taker to disconnect a call when the call is in an off hook status at the calling parties end. This eliminates the possibility that emergency resources are needlessly tied up by emergency calls made and then left off hook [2].

**M25: Called party hold:** This feature allows a call taker to continue to stay connected to the calling party even if the calling party attempts to place their phone in an on-hook status [2].

**M26: Caller ring back:** This will allow the call taker to be able to ring a phone back even if the destination phone is in an off-hook status [2].

## 5 End-to-End IP-Based Emergency Calls

End-to-end emergency calls originate on an Internet device, traverse IP networks and terminate on an IP-capable ECC (IECC).

As noted, emergency calls need to be identified as such (Section 5.1) and be routed to the appropriate emergency call center (Section 5.2). The ECC needs to determine who (Section 5.3) placed the call from where (Section 5.4). Emergency calls may not be subject to access restrictions placed on non-emergency calls. Also, some call features may interfere with emergency calls, particularly if triggered accidentally (Section 6).

### 5.1 Emergency Address

The emergency address is used by the emergency caller to declare a call to be an emergency call and to guide the call to an ECC. The emergency address could a be “sip”, “sips” or “tel” URI, or some other, yet-to-be-defined URI scheme.

**A1: Universal:** Each device and all network elements MUST recognize one or more global emergency call identifiers, regardless of the location of the device, the service provider used (if any) or other factors.

SIP is not specific to one country or service provider and devices are likely to be used across national or service provider boundaries. Since services such as disabling mandatory authentication for emergency calls (S1) requires the cooperation of outbound proxies, the outbound proxy has to be able to recognize the emergency address and be assured that it will be routed as an emergency call. Thus, a simple declaration on a random URI that it is an emergency call will likely lead to fraud and possibly attacks on the network infrastructure. A universal address also makes it possible to create user interface elements that are correctly configured without user intervention. UA features could be made to work without such an identifier, but the user interface would then have to provide an unambiguous way to declare a particular call an emergency call.

**A2: Local:** Since many countries have already deployed national emergency numbers, such as 911 in North America and 112 in large parts of Europe, UAs, proxies and call routers MUST recognize local emergency numbers. In addition, they SHOULD recognize emergency numbers that are found elsewhere.

The latter requirement is meant to help travelers that may not know the local emergency number and instinctively dial the number they are used to from home. However, it is unlikely that all systems could be programmed to recognize any emergency number used anywhere as some of these numbers are used for non-emergency purposes, in particular extensions and service numbers.

**A3: Recognizable:** Emergency calls **MUST** be recognizable by user agents, proxies and other network elements. To prevent fraud, an address identified as an emergency number for call features or authentication override **MUST** also cause routing to an ECC.

**A5: Minimal configuration:** Any local emergency numbers **SHOULD** be configured automatically, without user intervention.

A new UA “unofficially imported” into an organization from elsewhere should have the same emergency capabilities as one officially installed.

**A6: Secure configuration:** Devices **SHOULD** be assured of the correctness of the local emergency numbers that are automatically configured.

If we assume a fixed, global emergency service identifier that requires no configuration and only configure local “traditional” emergency numbers, users are not likely to suddenly dial some random number if a rogue configuration server introduces this as an additional emergency number. The ability to override all locally configured emergency number is of more concern.

**A7: Testable:** A user **SHOULD** be able to test whether a particular address reaches emergency help, without actually causing emergency help to be dispatched or consuming ECC call taker resources.

## 5.2 Identifying the Appropriate Emergency Call Center

From the previous section, we take the requirement of a single (or small number of) emergency addresses which are independent of the caller’s location. However, since for reasons of robustness, jurisdiction and local knowledge, ECCs only serve a limited geographic region, having the call reach the correct ECC is crucial. While an ECC may be able to transfer an errant call, any such transfer is likely to add tens of seconds to call setup latency and is prone to errors. (In the United States, there are about 5,000 PSAPs.)

There appear to be two basic architectures for translating an emergency address into the correct IECC. We refer to these as caller-based and mediated. In *caller-based resolution*, the caller’s UA consults a directory and determines the correct IECC based on its location. We assume that the UA can determine its own location, either by knowing it locally or asking some third party for it. A UA could conceivably store a complete list of all ECCs across the world, but that would require frequent synchronization with a master database as ECCs merge or jurisdictional boundaries change.

For *mediated resolution*, a SIP (outbound) proxy or redirect server performs this function. Note that the latter case includes the architecture where the call is effectively routed to a copy of the database, rather than having some non-SIP protocol query the database. Since servers may be used as outbound proxy servers by clients that are not in the same geographic area as the proxy server, any proxy server has to be able to translate any caller location to the appropriate ECC. (A traveller may, for example, accidentally or intentionally configure its home proxy server as its outbound proxy server, even while far away from home.)

Note that the first proxy doing the translation may not be in the same geographic area as the UA placing the emergency call.

The problem is harder than for traditional web or email services. There, the originator knows which entity it wants to reach, identified by the email address or HTTP URL. However, the emergency caller only dialed an emergency address. Depending on the location, any of several ten thousand ECCs around the world could be valid. In addition, the caller probably does not care which specific ECC answers the call, but rather that it be an accredited ECC, e.g., one run by the local government authorities. (Many ECCs are run by private entities. For example, universities and corporations with large campuses often have their own emergency response centers.)

**I1: Correct IECC:** The system **MUST** reach the correct IECC, that is, an IECC that serves the location of the caller. In particular, the location determination should not be fooled by the location of IP telephony gateways or dial-in lines into a corporate LAN (and dispatch emergency help to the gateway or campus, rather than the caller), multi-site LANs and similar arrangements.

**I2: Early routing:** In mediated mode, the first proxy server along a request path **MUST** attempt to route the call to the appropriate IECC.

Proxy servers close to the caller can be expected to have better call routing knowledge, particularly if international boundaries are being crossed.

**I3: Choice of IECCs:** The system **SHOULD** offer the emergency caller a choice as to whether he wants to reach a local private emergency response center, e.g., on a corporate campus, or the government-run emergency call center responsible for his current location.

This choice is often, but not always, provided today. For example, in some cases, the local campus emergency center is reachable by a different number or 9-911 reaches the external ECC, while 911 reaches campus security.

**I4: Assuring IECC identity:** The emergency caller **SHOULD** be able to determine conclusively that he has reached an accredited emergency call center.

This requirement is meant to address the threat that a rogue, possibly criminal, entity pretends to accept emergency calls.

Implementations **SHOULD** allow callers to proceed, with appropriate warnings or user confirmations, if the identity of the destination IECC cannot be verified.

Verification can fail for any number of reasons, such as lack of a common certificate chain, especially when traveling, call forwarding, or the expiration of certificates. Accreditation, e.g., in the case of corporate or university campuses, may not exist.

**I5: Traceable resolution:** Particularly for mediated resolution, the caller **SHOULD** be able to definitively and securely determine who provided the resolution answer.

**I6: Assuring directory identity:** The querier (UA or server) **MUST** be able to assure that it is querying the intended directory.

**I7: Query response integrity:** The querier **MUST** be able to be confident that the query or response has not been tampered with.



**I8: Assuring update integrity:** Any update mechanism for the directory **MUST** ensure that only authorized users can change directory information. An audit trail **MUST** be provided.

**I9: Call setup latency:** The directory lookup **SHOULD** add minimal delay to the call setup. Since outbound proxies will likely be asked to resolve the same geographic coordinates repeatedly, a suitable time-limited caching mechanism **SHOULD** be supported (see also "Ix").

**I10: Multiple directories:** A UA or proxy **SHOULD** be able to use multiple different directories to resolve the emergency address. We do not assume that a single directory has worldwide or even nationwide coverage.

This allows competing or regional data sources.

**I11: Referral:** All directories **SHOULD** refer out-of-area queries to an appropriate default or region-specific directory.

This requirement alleviates the potential for misconfigurations to cause calls to fail, particularly for caller-based queries.

**I12: Multiple protocols:** It **MAY** be useful if directories support multiple query protocols, such as SIP (for proxying), LDAP, a SOAP-based query and others. A mandatory-to-implement protocol **MUST** be specified.

It appears likely that the resolution mechanism will be needed by a variety of session protocols and user applications.

**I13: Robustness:** The resolution mechanism **MUST** allow to deploy systems that are robust in the face of partial network and directory server failures. Caching **MAY** be used to mitigate temporary unavailability of directories or network connectivity.

**I14: Incrementally deployable:** An Internet-based emergency call system **MUST** be able to deployed incrementally. In the initial stages of deployment, an emergency call may not reach the optimal ECC.

### 5.3 Identifying the Caller

Enhanced emergency call systems provide the ECC with the identity and location of the caller. In PSTN-based systems, the identity is represented by the number of the terminal the call is placed from. In a SIP-based system, we have two distinct identities, namely the address of the terminal (**Contact** header field) and the identity (name and/or AOR) of the person using the terminal. Depending on the circumstances, only one of them may be available. For example, from a public terminal ("Internet payphone"), only the **Contact** address may be useful.

In most jurisdictions, callers do not have a choice as to whether they want to reveal their location or identity; such disclosure is typically mandated by law.

**C1: Identity:** The system **SHOULD** allow to identify both the caller's identity and his or her terminal address.

**C2: Privacy override:** The end system **MUST** be able to automatically detect that a call is an emergency call so that it can override any privacy settings that conflict with emergency calling. (Whether this override can be configured by the user or is considered a condition of service is considered a legal matter, not a protocol issue.)

Since emergency calls are often placed by children, by people using somebody else's end system or by people in panic, any configuration should be automated rather than relying on user interaction at the time of the call. Delaying a call until the user discovers that they have to answer some screen prompt or deal with a voice prompt in an unfamiliar language is likely to lead to large call setup delays or call failures. This does not preclude that end systems can allow, on a call-by-call basis, to configure special call parameters.

## 5.4 Identifying the Caller Location

This section supplements the requirements outlined in [3]. Thus, the requirements enumerated there are not repeated here. In general, we can distinguish two modes of operation: *direct* and *indirect* location provision. In *direct* location provision, the calling end system knows its own location and can convey this location to the ECC. In an indirect system, the caller is identified by a permanent or temporary identifier, which the ECC then uses to map the caller to a current location. (In the current North American enhanced emergency calling system, the landline terminal phone number is mapped to a location using the so-called ALI (Automatic Location Identification) database. For wireless phones, a temporary identifier is created and then mapped to the location information.)

(This is somewhat similar to terminal-based and network-based location services in wireless "911" services. However, even in direct location provision, the terminal may well acquire the location information from a third party, e.g., a wireless location beacon or a DHCP server.)

**L1: Multiple location providers:** For indirect locations, ECCs **MUST** be able to access different location providers. The location provider may be tied to the service provider or may be independent of the service provider.

This requirement avoids that all users have to rely on a single location provider. This requirement is hard to avoid if there are no traditional national application-layer service providers.

**L2: Civil and geographic:** Where possible, both civil (street address) and geographic (longitude/latitude) information **SHOULD** be provided.

While geographic information can usually be translated into civil coordinates, some coordinates, such as building numbers and floors, are more easily provided as civil coordinates since they do not require a detailed surveying operation. For direct location determination, it may also be easier for the user to check civil coordinates for correctness.

## 6 Call Setup and Call Features

**S1: Authentication override:** In many jurisdictions, emergency calls can be placed by any device, regardless of whether it has subscribed for service. Similarly, outbound proxies and other call filtering elements **MUST** be able to be configured so that they allow unauthenticated emergency calls.

**S2: Mid-call features:** The end system **MUST** be able to recognize an emergency call and allow configuration so that certain call features are not triggered accidentally. For example, it may be inappropriate

to transfer the ECC or put it on hold. An end system MAY make it more difficult to disconnect an on-going emergency call or accept other incoming calls while in an emergency call.

Call transfer initiated by the emergency caller is likely only to be a problem if a PSTN gateway or B2BUa is in the call path. It is not clear how much effort should be expended on preventing intentional, as opposed to accidental, disconnection, since callers can typically find physical-layer means to terminate the call.

**S3: Testable:** Users SHOULD be able to test the ability to place an emergency call without actually invoking an emergency response.

This capability is unfortunately missing from the current PSTN.

**S4: Integrity:** Implementations MUST provide mechanisms that ensure the integrity of SIP protocol component that are crucial to providing reliable emergency call service.

## 7 Security Considerations

Confidentiality, integrity and authentication are core requirements for multiple aspects of emergency calling. Threats exist at the infrastructure and individual call level. Security threats are identified throughout this document.

An adversary could corrupt call information or ECC resolution to cause emergency calls to fail subtly, without the caller necessarily noticing. This can be done on a call-by-call basis or by corrupting elements that perform the resolution, including the directory described in Section 5.2, Internet routing tables or DNS. (Obviously, there are typically other ways to make emergency calls fail completely, an approach phone-wire cutting burglars have practiced for years. However, the ability to spoof an ECC requires physical access to the PSTN cable plant, while this may not be required in the IP case.)

Here, we do not consider attacks on the emergency call infrastructure itself. The techniques for dealing with such attacks are likely to be similar as those for protecting other network infrastructure, although the stakes may well be higher.

## 8 References

### Normative References

- [1] S. Bradner, "Key words for use in rfc's to indicate requirement levels," RFC 2119, Internet Engineering Task Force, Mar. 1997.
- [2] National Emergency Number Association (N. E. NA) Migration Working Group of the Network Technical Committee, "NENA technical information document on the interface between the E9-1-1 service providers network and the Internet protocol (IP) PSAP," tech. rep., National Emergency Number Association (NENA), Coschocton, Ohio, Feb. 2003.
- [3] J. Cuellar, J. Morris, and D. Mulligan, "Geopriv requirements," internet draft, Internet Engineering Task Force, Jan. 2003. Work in progress.

## Informative References

- [4] N. Charlton, M. Gasson, G. Gybels, M. Spanner, and A. van Wijk, "User requirements for the session initiation protocol (SIP) in support of deaf, hard of hearing and speech-impaired individuals," RFC 3351, Internet Engineering Task Force, Aug. 2002.
- [5] H. C. Folts, C. Beard, and K. Carlberg, "Requirements for emergency telecommunication capabilities in the Internet," internet draft, Internet Engineering Task Force, Oct. 2002. Work in progress.

## 9 Acknowledgments

James Polk provided helpful comments.

## 10 Authors' Addresses

Henning Schulzrinne  
Dept. of Computer Science  
Columbia University  
1214 Amsterdam Avenue  
New York, NY 10027  
USA  
electronic mail: [schulzrinne@cs.columbia.edu](mailto:schulzrinne@cs.columbia.edu)

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.