A Framework for Scalable Global IP-Anycast (GIA)

Dina Katabi, John Wroclawski

MIT Laboratory for Computer Science
545 Technology Square
Cambridge, MA 02139

{dina,jtw}@lcs.mit.edu

ABSTRACT

This paper proposes GIA, a scalable architecture for global IP-anycast. Existing designs for providing IP-anycast must either globally distribute routes to individual anycast groups, or confine each anycast group to a pre-configured topological region. The first approach does not scale because of excessive growth in the routing tables, whereas the second one severely limits the utility of the service. Our design scales by dividing inter-domain anycast routing into two components. The first component builds inexpensive default anycast routes that consume no bandwidth or storage space. The second component, controlled by the edge domains, generates enhanced anycast routes that are customized according to the beneficiary domain's interests. We evaluate the performance of our design using simulation, and prove its practicality by implementing it in the Multi-threaded Routing Toolkit.

Keywords: Anycast, Routing, Scalable, Internet, Architecture

1. INTRODUCTION

IP-anycast is a network service that allows a sender to access the nearest of a group of receivers that share the same anycast address, where 'nearest' is defined according to the routing system's measure of distance. Usually the receivers in the anycast group are replicas, able to support the same service (e.g., mirrored web servers). Thus, accessing the nearest receiver enhances the performance perceived by the sender, saves the network's bandwidth, and provides the desired service. Figure 1 illustrates IP-anycast.

Anycast has numerous potential applications. RFC 1546 [25] proposes anycast as a means to discover a service location and provide host auto-configuration. For example, by assigning the same anycast address to a set of replicated FTP servers, a user downloading a file need not choose the best server manually from the list of mirrors. The user can use the anycast address to directly download the file from the nearest replica.[1] The application of anycast to host auto-configuration, on the other hand, is exemplified in the assignment of the same anycast address to all Domain Name Servers (DNS). In this case, a host that is moved to a new network need not be reconfigured with the local DNS address. The host can use the global anycast address to access the local DNS server anywhere. Recently, IP-anycast has been proposed as an infrastructure for multicast routing. For example, Kim et al. use anycast to allow Protocol Independent Multicast Sparse Mode (PIM-SM) to support multiple rendezvous routers per multicast tree [17], while Katabi uses anycast in designing an intra-domain multicast routing protocol that reduces bandwidth consumption and alleviates traffic concentration [14].



Figure1: Illustration of IP-anycast

Although Sender 1 and Sender 2 are sending to the same anycast address (Group A), the network delivers each packet to the group member nearest its sender.

Currently, there is no scalable design for global IP-anycast. The traditional approach routes anycast addresses using the unicast routing protocols, a design decision that makes anycast unscalable. Unicast routing scales by aggregating routes to destinations that share the same prefix into one routing entry (CIDR [8]). Anycast, on the other hand, defies this form of hierarchical aggregation. An anycast address, like a multicast address, represents a group of nodes that share a particular characteristic and exist somewhere in the Internet. There is no reason to expect anycast group topology to be hierarchical or to comply with the unicast topology. Therefore, routing anycast using the unicast routing protocols requires advertising each global anycast address separately. This requirement causes the routing tables to grow proportionally to the number of all global anycast groups in the entire Internet, and hence does not scale. Figure 2 illustrates anycast's defiance of hierarchical aggregation.

This paper proposes GIA, a scalable architecture for global IP-anycast. GIA scales by capturing the special characteristics of the anycast service in its inter-domain routing protocol, which

This research was supported by the US Defense Advanced Research Projects Agency (DARPA) under contract number N66001-98-1-8903.

[1] Methods for the use of anycast for TCP-based services, as in this example, are discussed in [1] and [25].



Figure 2: Anycast's defiance of hierarchical aggregation. A1 and A2 are members of the same anycast group. If the group's address shares the prefix with Domain 1 then Domain 2 cannot aggregate the anycast address in its prefix and should advertise it as a separate entry in BGP. A similar situation arises if the group's address shares the prefix with Domain 2.

generates two types of routes: 1) default inexpensive routes that consume no bandwidth or storage space; 2) enhanced shortest path routes that are customized according to the beneficiary domain's interests. Although the architecture is described assuming that a path's length is measured using the unicast measure of distance (number of hops), we show in Section 5 that GIA can use other measures of distance such as average latency or available bandwidth.

The paper is organized as follows. The next section provides a discussion of related work. Section 3 provides a general overview of the design. The details of our address architecture and routing protocols are described in Section 4. Section 5 shows GIA's ability to use a variety of distance measures. Section 6 discusses performance and overhead. A brief description of our implementation of a GIA-enabled border router is provided in Section 7. Deployment is addressed in Section 8. Finally, Section 9 presents our conclusion.

2. BACKGROUND AND RELATED WORK

Anycast was defined in 1993 by RFC 1546 [25]. The document proposes anycast as a means for service discovery and host auto-configuration. It recommends assigning anycast its own address space. It also points out the major difficulties challenging the deployment of IP-anycast. The first difficulty is anycast's defiance of hierarchical aggregation, which makes the service hard to scale. The second difficulty is the stateless nature of the service, an issue that makes the establishment of TCP connections on top of anycast addresses problematic. The RFC proposes a mechanism for establishing TCP connections to anycast destinations; however, it leaves the scalability issue unresolved.

Anycast has been adopted by all proposed successors of IPv4: Pip [6], SIPP [11], and IPv6 [13]. In particular, IPv6 allocates anycast addresses from the unicast address space, making them indistinguishable from their unicast counterparts. Each anycast group is confined to a particular topological region with which it shares the address prefix. Within the region identified by the shared prefix, each member of the anycast group is advertised as a separate entry in the unicast routing system. Outside that region, the anycast address may be aggregated into the routing advertisement for the shared prefix. By confining each anycast group to a predetermined region, IPv6 lessens anycast's scalability problem but does not solve it. Global anycast groups still must be advertised as separate routing entries throughout the entire Internet. These global groups are necessary for many anycast applications, such as the ones in [1,25]. Moreover, they are desirable even in situations where the group members are currently located in a confined region. An example of such situation would be a company that provides an online service and uses an anycast address to have its customers access the nearest online office. Although the company online offices might cover only the US, the company would still want to use a global address, since a scoped anycast address prevents future expansion to Europe and Asia.

Also related to our work are proposals for providing an anycast service at the application layer [2,4,7,22,27]. This approach attempts to build a directory system which, queried with a service name and a client address, returns the unicast address of the server that is nearest the client and that supports the service. Application layer anycast has both advantages and disadvantages over IP anycast. The first disadvantage is that application layer anycast exhibits several complications and scalability problems. More specifically, providing an anycast service at the application layer requires collecting two types of information: 1) information about the servers that are up and supporting a particular service, 2) information about the distance between each potential client and the different servers measured using the metric of interest. To obtain the first type of information, the anycast directory needs either to repeatedly probe the servers or to have the servers repeatedly report their availability to the directory. Given the potentially huge number of services and servers, both mechanisms create a substantial overhead on the network and the directory. Obtaining the distance information is also problematic. For example, if distance is measured by the average network latency, then we need to probe the client from the server or a system collocated with the server to discover the path latency. Similarly, if distance is measured by the number of hops then we need to traceroute the client from the server. In comparison, in IP-anycast, a server's availability is discovered by its local router and the distance information gets updated naturally as part of the routing protocol. Another disadvantage of application layer anycast is its inability to satisfy some classes of anycast applications such as using anycast as an infrastructure for multicast routing [14,17]. A third disadvantage of application layer anycast is its lack of a bootstrap mechanism whereby users access the nearest anycast directory. On the other hand, application layer anycast has two main advantages. First, it is easier to deploy than IP-anycast because it does not involve modifying the routers. Second, it can use distance metrics that are available only at the application level such as the server load. The authors believe that both IP-anycast and application layer anycast deserve further research to fully understand their capabilities and determine their future. Providing a scalable architecture for IP-anycast is a step towards that end.

3. DESIGN RATIONALE

We think the traditional belief that IP-anycast should be routed similarly to unicast has hampered the acceptance and deployment of anycast. The anycast routing protocol should rather recognize the characteristics of IP-anycast and benefit from them to scale. Forcing anycast to obey the unicast routing paradigm wastes routing resources. For example, it is inefficient for a router at a US university (e.g., MIT) to spend equal amounts of routing resources on the route to the Yahoo site and the route to London's Public Transportation site. The first route is used every minute by users in the university, whereas the second one is rarely if ever used. Thus, at a particular edge domain, anycast routes are not equally valuable, and a good anycast routing protocol devotes more resources to frequently accessed anycast groups.

Furthermore, an anycast group represents a network service. In computer systems, it is a common practice to scale services by caching. For example, the Web, a network service, scales by caching repeatedly accessed documents in a community at a local proxy. Similarly, it is likely that at any given time there is a predictable set of anycast groups that users in a domain access with high probability, and that this set is much smaller than all anycast groups in the entire Internet. Anycast can scale by caching at each edge domain routes to groups frequently accessed by the domain's users.

GIA's design allows an edge domain to discover, store and maintain efficient routes to anycast groups repeatedly accessed by users in the domain, while supporting an inexpensive fallback mechanism to send packets to unpopular groups. In fact, the fallback mechanism does not consume any bandwidth or storage space because it is based on mapping the anycast topology to the underlying unicast topology. This design scales for the following reasons. First, it prevents wasting routing resources on rarely used routes, which scarcely affect the perceived performance of the service. Second, by pushing most of the work to the edge domains where routers have small routing tables and many free CPU cycles, it provides a good topological alignment between workload and resources. Finally, because each edge domain spends its routing resources on the anycast routes repeatedly accessed by its own users, it places the workload on the domain that derives the benefits. This creates incentive for edge domains to control the number of their anycast routes to stay within the limits of the available routing resources.

4. DESIGN DETAILS

This section describes the details of the architecture.

4.1 Address Architecture

GIA assigns anycast its own address space. Thus, as illustrated in Figure 3, an anycast address starts with a fixed length bit-pattern that identifies anycast addresses from their unicast and multicast counterparts. We call this prefix the 'Anycast Indicator'.

GIA allocates anycast addresses to domains according to their allocated unicast address space. Hence, the second field in an anycast address is the unicast prefix of the Internet domain that owns the anycast address. We call this field the 'Home Domain Prefix'. It has a variable length that depends on the size of the domain's unicast address space. GIA requires that the home domain contain at least one member of the anycast group. Note that the anycast address is still global and can be assigned to machines anywhere in the Internet.

The last field in an anycast address is the group ID. It has a variable length and it identifies a particular group among the anycast groups that share the same home domain.

The address architecture as it is described above allocates to every Internet domain an anycast address space proportional to its unicast address space.[2] A domain might use its allocated anycast addresses to provide global services. Alternatively, the domain might lease some of its anycast addresses to end users providing online services, or even to other domains. For example, assume *x* is a company that provides an online service and that wants its customers to use an anycast address to locate the online office nearest to them. It is likely that company *x* has a main office connected to the Internet somewhere. Thus, it can use one of the anycast addresses associated with its network for its online service. In this case the home domain for the anycast group is company *x's* domain. On the other hand, if company *x* does not have its own domain, it can lease an anycast address from its service provider, in which case the group's home domain is the provider's domain. In either case, if company *x* grows in the future and opens a new online office, the new office can use the same anycast address and be accessible to customers in its neighborhood.

Anycast Indicator (fixed length)	Home Domain's Unicast Prefix (variable length)	Group ID (variable length)

Figure 3: The syntax of an IP-anycast address

Finally, well-known anycast addresses used for host auto-configuration (such as the group of all DNS servers) should have their home domains in one of the backbones or as virtual domains advertised by the backbones.

4.2 Address Assignment

The process according to which a domain assigns an anycast address to an end user is domain-dependent and can be the same as the one used for assigning unicast addresses. For example, the anycast address might be assigned manually by the administrator or by special address assignment servers that lease anycast and unicast addresses to end users. In addition, the Internet Assigned Numbers Authority (IANA) will assign a set of well-known anycast addresses to a variety of host auto-configuration groups.

4.3 Joining an Anycast Group

To join an anycast group, a host asks its first hop router to advertise the group's address on its behalf. This communication can be achieved by adding a new message type to either the Internet Group Management Protocol [5] or the Neighbor Discovery Protocol [23]. The router advertises the address according to the anycast routing protocol adopted by the domain. It uses a keep-alive mechanism to ascertain the availability of the anycast member, and never advertises an address after the member becomes inaccessible. In addition, the router will likely use a security procedure to ensure that the host is allowed to join the anycast group, as allowing uncontrolled joins to anycast groups creates the potential for a denial of service attack.

4.4 Anycast Routing

We begin this section by providing some useful definitions, then we describe the details of our routing protocols.

4.4.1 Definitions

Domain: throughout this paper we use the word 'domain' to refer to a routing domain or an autonomous system (AS).

[2] One possible anycast indicator is the bit-pattern '11110'. For the case of IPv4, this choice of the anycast indicator means that domains whose unicast prefix is smaller than x.x.x.x/27 are not allocated any anycast address space. However, domains whose unicast space is smaller than x.x.x.x/27 are a special case and are usually behind a Network Address Translator. These domains can lease or buy anycast addresses from other domains.



(a) Classification of anycast groups at an end domain

(b) From the perspective of MIT, FreeBSD is internal, Yahoo is popular and London's Public Transportation site is unpopular (the arrows represent anycast packets).

Figure 4: Anycast group classification at an edge domain

Neighborhood of a Domain: the neighborhood of a domain of radius H is the set of domains that are H or fewer domain hops away.

Anycast Group Classification: an edge domain (stub domain) classifies an anycast group according to the following rules, which are illustrated in Figure 4.

- An internal anycast group is a group for which the domain has internally at least one member. Note that all groups are internal to their home domain. However, groups might be internal to domains other than their home domains.
- An external anycast group is a group for which the domain has no local members.
- A popular anycast group is an external group that users in the domain frequently access.

4.4.2 Routing Internal Anycast Groups

GIA routes internal anycast groups the traditional way using unicast routing. Intra-domain routing protocols based on the distance-vector algorithm, such as RIP, intrinsically have the ability to provide an anycast service; if run in a network where the same address is assigned to multiple destinations, they simply route to the nearest one [25]. For protocols based on the link-state algorithm to work correctly, routers should abstain from routing through an anycast address. Figure 5 illustrates an example of this problem. Assuming A is an anycast group, router R1 should not mistake the topology in 5-a for that in 5-b and should not try to route packets sent to R5 through A. To solve the problem, a large cost is assigned to virtual links connecting anycast nodes to their local networks, such that they are not used in building routes unless the anycast node is the destination.



Figure 5: Applying the link state algorithm directly may introduce false topologies

Although routing internal groups using the unicast intra-domain routing protocol causes each internal group to consume an entry in the internal routing table, this approach stays scalable because the number of internal groups is controllable by the domain itself. Therefore, each domain can keep this number within the limits of the locally available bandwidth and storage space.

Finally, in contrast to unicast routing, internal groups are not advertised to other domains in the Internet. Sections 4.4.3 and 4.4.4 describe how users in other domains access those groups. (For those users the groups are external.)

4.4.3 Routing Unpopular Anycast Groups

In GIA, unpopular anycast groups need not be routed. The number of unpopular groups is likely to grow much larger than the number of popular groups. Thus, by using inexpensive default routes to forward packets addressed to unpopular groups, the system, without degrading the service, makes large savings.

A default route does not consume any bandwidth to be generated and does not need any storage space in the routing tables. To understand how such a route exists recall that an anycast address is a concatenation of the anycast indicator, the unicast prefix of the home domain and the group ID. Also, recall that the architecture requires the provider of the anycast service to have at least one member in the home domain. Hence, a router that receives an anycast packet addressed to an unpopular group forwards the packet to the group member in the home domain. To do so the router assigns the destination address to a lookup variable, and shifts the anycast indicator off the variable. After the shifting operation, the address in the variable is a unicast address from the unicast address space of the home domain. The router looks up the variable in its unicast routing table and forwards the packet to the corresponding next-hop, which points towards the home domain. Note that the router leaves the destination address in the packet intact so that other routers that don't have a route for this group may follow exactly the same procedure. Figure 6 shows how an unpopular anycast group is mapped to a unicast address in its home domain.

Thus, a packet addressed to an unpopular group is forwarded towards its home domain. However, depending on the popularity distribution of its corresponding group, the packet follows one of three possible paths. First, if the packet crosses any domain that contains a member of the anycast group then the packet is



Figure 6: Mapping an unpopular anycast group to a unicast address in the home domain. The anycast destination is assigned to a lookup variable. The anycast indicator is shifted off the variable, then the variable is looked up in the router's unicast routing table. The anycast packet remains intact.

delivered to that member by the intra-domain anycast routing protocol. Second, if the packet crosses a domain that has this group as a popular group and consequently knows a shorter route to one of the group's members, then the packet continues its journey along the shortest path. Finally, if neither of the aforementioned cases is encountered, then the packet eventually hits the home domain and is delivered to the member there.

4.4.4 Routing Popular Anycast Groups

At the core of GIA's architecture is generating shortest path routes to popular anycast groups. We begin by giving a general overview of this process, and we provide the details in the next sections. To generate routes to popular groups, the border routers in an edge domain decide which groups are popular in their domain. This decision is made according to the route's level of usage or the domain's policy. Periodically, border routers search their neighborhood looking for the nearest members of popular anycast groups. Once they find the shortest path route to a popular anycast group, they cache the route and tunnel all subsequent packets to the domain where the nearest member resides.

In contrast to unicast inter-domain routing, which is based on advertising unicast prefixes to all Internet domains, GIA adopts an on-demand query-based inter-domain routing protocol. We choose a query-based protocol for two reasons. First, we want a design in which routers in the core of the Internet do not store any anycast routes.[3] Second, the fact that an anycast group is replicated in multiple domains in the Internet increases significantly the probability of finding the nearest group member by exploring a small neighborhood around the interested domain. (Section 6.1 shows that this increase is exponential.)

Our route learning process makes use of the TCP connections a BGP router has with its peers [26]. It involves adding two new messages to BGP: a search message and a reply message. In the following sections we describe the steps of learning anycast routes.

4.4.4.1 Initiating a search

To discover which groups are popular in their edge domain, the border routers observe the number of packets recently sent to each anycast group. In addition, the border routers might be configured to consider certain groups as popular regardless of their access level. For example, the BRs in a domain that has no DNS server might be configured to consider the group of all DNS servers as a popular group regardless of its access level. Note that because all anycast packets addressed to a particular group exit the domain at the same border router, each BR decides on the access level of the anycast groups it sees without contacting the other BRs.[4]

[3] This objective makes it hard to design an advertisement-based routing protocol, because these protocols prevent flooding by storing at each router the shortest route seen so far. Consider unicast routing as an example. If routers in the backbones do not store unicast routes then any insignificant change in the topology will be flooded to all domains in the Internet because the upstream routers cannot tell whether the change in the topology would affect the forwarding path at downstream routers. This flooding effect would be exacerbated by the fact that an anycast address has a virtual high connectivity caused by its replication [18].

[4] In case the border routers are too busy to monitor the access level of anycast groups, a separate device attached to the same link as the border routers can do the job.



Figure 7: The Format of the search message

A search for a popular anycast group is triggered by the exit border router towards the group's home domain, which receives the anycast packets in the absence of a learned route. We call this border router the originating border router (OBR). At the beginning of each 'Search Interval', the OBR generates a search message for all of the popular groups for which there is no learned route and broadcasts it to all of its peers. The duration of the 'Search Interval' decides the maximum search rate and can be agreed upon with the domain's provider. Once the search is generated the OBR sets a timer and waits for replies. Note that during the search process the OBR does not keep the arriving anycast packets until a route is learned. It forwards them along the default route.

The search is a scoped domain-by-domain broadcast that explores the neighborhood around the searching domain looking for members of popular anycast groups. The search message has the format shown in Figure 7. The message has fields similar to a BGP update. In particular, it contains a path-vector field, which collects information about the autonomous systems the search crosses and prevents the search message from looping. (To comply with BGP's terminology, Figure 7 refers to the path-vector as Path Attributes.) In addition the message contains a TTL field, which scopes the search to a neighborhood around the searching domain. This field is initialized to the maximum number of domain hops the search can traverse, and gets decreased with each domain hop. Note that one search message may solicit routes for many popular anycast groups.

4.4.4.2 Receiving a search

The rules for processing a received search message are illustrated in Figure 8. A search message needs to be processed only once in each domain; thus, a border router (BR) that receives a search from an internal peer propagates the message to all of its peers with no further processing.[5] A BR that receives a search message from an external peer examines whether the domain has routes to the anycast addresses in the message. The BR can reply for two types of groups: internal groups, and popular groups for which it has already learned routes. For all groups that are internal to the replying BR's domain, the BR sends a reply message, which relays the path-vector in the original search message after appending the receiving BR's autonomous system number (AS number). In addition, the reply includes the original search sequence number and the receiving BR's IP-address. The reply is sent directly to the OBR.

[5] Since all BRs in a domain have the same routing table, a search needs to be processed only once in each domain.



Figure 8: Receiving a search message (simplified by assuming the search message contains 1 address)

Groups for which no internal member is found are looked up in the set of learned anycast routes. For each anycast group for which the receiving BR has a learned route, it concatenates the path-vector in the search with the path-vector of the learned anycast route, and sends the resulting path-vector to the OBR in a reply message. The replier field in the reply message is set to the IP address of the router from which the cached route has been learned. All addresses for which the receiving BR is able to send a reply are removed from the search message. If the message still contains anycast groups for which no route has been found, the receiving BR decrements the TTL of the search, checks that the TTL did not reach zero, and propagates the search to all of its peers.

To prevent a search message from looping, GIA requires a BR that receives a search message whose path-vector includes its own AS to ignore the message. Moreover, to reduce the number of messages spawned by a search, we require each BR to maintain a table of all triples (OBR, sequence number, shortest path-vector for this combination of OBR and sequence number) seen recently (e.g., in the last two average search intervals). A BR propagates a search only if it contains a path-vector shorter than the shortest path-vector with the same (OBR, sequence number) seen so far. Although storing a table of the above-mentioned triples consumes some memory at a border router, the size of the memory needed is relatively small because it is on the order of the number of OBRs in a neighborhood. In addition, the lookups in this table are not on the critical path of unicast data packets.

4.4.4.3 Receiving a reply

After sending a search message, an OBR sets a timer and waits for replies. When the timer expires, the OBR checks all the received replies and chooses the one with the smallest path-vector (the shortest route). The OBR checks its list of pending popular addresses and deletes any address for which it has found a route. The groups the router searched for but for which it couldn't find the nearest members have their popularity multiplied by a decaying factor to reduce their chance of being included in a future search.

The learned routes are kept in a cache of popular anycast routes. Also, the routes are advertised to all internal peers as if they were learned from a BGP update message. Depending on the domain's policy the routes might be injected into internal routers' routing tables or kept only at border routers.

A stored external anycast route contains the path-vector, which lists the set of domains the route traverses, and the unicast address of the destination BR. Both entries are extracted from the reply message. The path-vector is used in answering search messages issued by neighboring domains looking for a route to this anycast group. The unicast address of the destination border router is used to tunnel all subsequent anycast packets to the domain that has the nearest group member. Figure 9 illustrates an instance of the route learning protocol.

4.4.4.4 Scoping a search

GIA scopes a search such that it is likely to find the nearest group member without flooding the Internet. We do so using two mechanisms. First, a domain that generates a search controls the size of the searched neighborhood by setting the TTL field in the search message. This field should be set such that the search can reach the core of the network. Given that virtually all domains are less than 3 domain hops from the core of the Internet [3], we recommend setting the TTL field to 2 or 3.

Second, transit domains control the scope of a search by instructing their border routers (BRs) not to propagate search messages to distant peers, where the word 'distant' refers either to geographical distance or poor connection. Figure 10 shows an example of a provider network that connects Europe with the US. The BRs in each continent do not propagate searches to the BRs in the other continent. Pruning such searches does not significantly



1. The OBR in domain 1 broadcasts to its peers a search message soliciting routes for popular groups A and B.
2. By inspecting its routing table, the BR in domain 2 discovers that there is a member of B in its domain, so it sends to the OBR a reply for B. However, since it has no route for A, it propagates to its peer the remainder of the search message, which contains only a search for A.
3. The search for A, hits the BR in domain 5, which has a learned route for A. So it concatenates the path-vector in the search message with the learned route it knows, and sends the resulting route to the OBR.
4. The BR in domain 3 does not have a route to either group so it propagates the search to its peer. When the search hits the BR in domain 4, the router recognizes both groups as internal to its domain and sends a reply for both A and B to the OBR.

Figure 9: Learning routes to popular anycast groups

ERROR: undefined
OFFENDING COMMAND: ;O

STACK: