World Wide Web: URL, HTML, HTTP

World Wide Web (WWW)

- created in 1989 at CERN by Tim Berners-Lee
- ideas (hypertext, information store) are much older
- linked retrieval of text, images, sounds, movies, …
- also executable programs (Java)
- predecessor: gopher
- hypertext = linking objects (text) *across a network*
- integrates data access protocols
- graphical browser ➠ Internet for non-techies
- currently most important Internet application (next to email)

WWW components

names: Universal Resource Locator (URL)

retrieval: Hypertext transfer protocol (HTTP)

hypertext: Hypertext markup language (HTML)

browser: retrieve URL via HTTP, ftp, telnet, …from server

server: stores objects for one or more host names

URL

scheme://*host*[:*port*]/*path*/[;*parameters*][#*fragment*][?*query*]

```
http://www.fokus.gmd.de:80/step/hgs/
http://www.research.att.com/cgi-bin/bibsearch_html?www
mailto:president@whitehouse.gov
```

scheme: http, ftp, gopher, telnet, mailto, news, …

host: host name or dotted quad

port: TCP port, if not default

path: file name path

parameters: for partial retrieval, etc.

fragment: named position in text

query: parameter for database queries

HTML

- simple document type for SGML (standard general markup language)
- describes document structure, not formatting (kind of…)
- provision for hyperlinks
- can be …
  - written by hand
  - generated by special authoring tools
  - translated from LaTeX, nroff, Microsoft Word, …

HTML structure

- `<tag parameter=value ...>` text `</tag>`
- uses ISO 8859-1 (including ä,ö,ü, etc.)
- can be searched locally (↔ PostScript)
- display reasonably on wide range of hardware (ASCII terminal, different resolutions, braille, audio output, …)
- has tables, but currently no mathematics
- some standardized (HTML 2.0), much vendor-introduced (Netscape)
- constantly evolving

HTML document structure

```
<HTML>
<HEAD>
<TITLE>Title of document</TITLE>
</HEAD>
<BODY>
The body of the document
</BODY>
</HTML>
```

HTML tags

- headings: `H1 ...H6`
- paragraph: `P`
- preformatted text: `PRE`
- quote: `BLOCKQUOTE`
- unordered list:

```
<UL>
<LI>first list item
<LI>second list item
</UL>
```

- ordered list

```
<OL>
<LI>first list item
<LI>second list item
</OL>
```

- definition list

```
<DL>
<DT>HTML
<DD>Hypertext markup language
<DT>HTTP
<DD>Hypertext transport protocol
</DL>
```

HTML phrase markup

- typographic elements (“how to show this”)
  - **bold**: `<B>bold</B>`
  - *italic*: `<I>italic</I>`
  - `teletype: <tt>text</tt>`
  - blinking text: `<blink>avoid!</blink>`
- idiomatic elements (“what is this”)
  - citation: `<cite>`
  - emphasis: `<em>`
  - strong emphasis: `<strong>`
  - variable: `<var>`
  - …

HTML miscellaneous

- horizontal rule: `<HR>`
- line break: `<BR>`
- automatic playback of sounds
- backgrounds
- frames
- font size changes
- …

HTML forms

- allows user to input text, select choices, …
- encoded as 'name1=value1&name2=value2'
- escape sequences for space (+) and non-alphanumeric characters
- returned as GET or POST (explained later)

```
<FORM METHOD="POST" ACTION="http://www.w3.org/sample">
Your name: <INPUT NAME="name" SIZE="48"><p>
Male: <INPUT NAME="gender" TYPE=RADIO VALUE="male"><p>
Female: <INPUT NAME="gender" TYPE=RADIO VALUE="female"><p>
Cities in which you maintain a residence:<p>
<ul>
<li>Kent <INPUT NAME="city" TYPE="checkbox" VALUE="kent">
<li>Miami <INPUT NAME="city" TYPE="checkbox" VALUE="miami">
</ul>
<p><INPUT TYPE=SUBMIT> <INPUT TYPE=RESET></FORM>
```

HTML links

- source: `<a href="url">word</a>` ➠ usually shown underlined and blue, followed when clicked on
- destination within document (#fragment):
  `<a name="frag">word</a>` ➠ not visible to user
- `<IMG SRC="jim.jpg" ALT="Jim's picture">` displays GIF, JPEG *concurrently*, without user intervention

HTTP

- simple ASCII-based transfer protocol
- methods:

  GET: retrieve object, no side effects

  HEAD: get descriptive information

  PUT: replace object on server

  others: PATCH, COPY, MOVE, …
- stateless ➠ every query independent
- one request ➠ one TCP connection (client opens, server closes) ➠ inefficient ➠ HTTP 1.1 connections
- uses ftp-style error codes

HTTP request

```
GET /index.html HTTP/1.0
Accept: text/html, */*
If-modified-since: Sat, 29 Oct 1994 19:43:31 GMT
Referer: http://www.w3.org/hypertext/
From: webmaster@w3.org
```

(empty line marks end of request)

HTTP response

```
HTTP/1.0 200 Document follows
Date: Wed, 31 Jan 1996 20:45:17 GMT
Server: NCSA/1.5
Content-type: text/html
Content-language: en
Last-Modified: Wed, 31 Jan 1996 20:00:10 GMT

<html>
<head>
...
</html>
```

(server closes connection)

HTTP access control

- client attempts access (GET, PUT, …) normally
- server returns

```
HTTP/1.0 401 Unauthorized
WWW-Authenticate: Basic realm="WallyWorld"
```

- client tries again

```
Authorization: Basic base64-encoded-user:password
```

- passwords in the clear ➠ not secure
- ➠ use challenge-response instead (using shared secret)

Caching and proxies

- avoid repeated transfers ➠ cache object in memory, disk or on a proxy
- proxy:
  - only for HTTP
  - receive normal HTTP request
  - check if available locally and still current (HEAD If-modified-since)
  - if not, retrieve, return to client and store
- also used for firewalls

Problems

- locations may change ➠ “dangling” pointers ➠ indirection (URNs)
- little descriptive information ➠ URC
- no privacy, strong authentication ➠ SSL (generic TCP), SHTTP
- finding objects ➠ directories, “spiders”
- caching, proxies ↔ charging, counting “hits”