

Fundamentals of Computer Systems

Caches

Martha A. Kim


Columbia University

Fall 2014


Illustrations Copyright © 2007 Elsevier

Computer Systems

Performance depends on which is slowest:
the processor or the memory system



Memory Speeds Haven't Kept Up




Our single-cycle memory assumption has been wrong since 1980.

Hennessy and Patterson. *Computer Architecture: A Quantitative Approach*. 3rd ed., Morgan Kaufmann, 2003.

Your Choice of Memories


Fast **Cheap** **Large**



On-Chip SRAM



Commodity DRAM



Supercomputer




Memory Hierarchy

An essential trick that makes big memory appear fast

Technology	Cost (\$/Gb)	Access Time (ns)	Density (Gb/cm²)
SRAM	30 000	0.5	0.00025
DRAM	10	100	1 – 16
Flash	2	300*	8 – 32
Hard Disk	0.1	10 000 000	500 – 2000

* Read speed; writing much, much slower

A Modern Memory Hierarchy




AMD Phenom 9600
Quad-core
2.3 GHz
1.1–1.25 V
95 W
65 nm

A desktop machine:


Level	Size	Tech.
L1 Instruction*	64 K	SRAM
L1 Data*	64 K	SRAM
L2*	512 K	SRAM
L3	2 MB	SRAM
Memory	4 GB	DRAM
Disk	500 GB	Magnetic

* per core

A Simple Memory Hierarchy



First level: small, fast storage (typically SRAM)



Last level: large, slow storage (typically DRAM)

Can fit a subset of lower level in upper level, but which subset?

Locality Example: Substring Matching

H i p h i p h o o r a y ! \0

h i p \0

Addresses accessed over time \longrightarrow
aka "reference stream"

h H h i h p h h h i i p p h h

temporal locality: if needed X recently, likely to need X again soon

spatial locality: if need X, likely also need something near X

Cache

Highest levels of memory hierarchy

Fast: level 1 typically 1 cycle access time

With luck, supplies most data

Cache design questions:

What data does it hold? *Recently accessed*

How is data found? *Simple address hash*

What data is replaced? *Often the oldest*



What Data is Held in the Cache?

Ideal cache: always correctly guesses what you want before you want it.

Real cache: never that smart

Caches Exploit

Temporal Locality

Copy newly accessed data into cache, replacing oldest if necessary

Spatial Locality

Copy nearby data into the cache at the same time
Specifically, always read and write a **block**, also called a **line**, at a time (e.g., 64 bytes), never a single byte.

Memory Performance

Hit: Data is found in the level of memory hierarchy

Miss: Data not found; will look in next level

$$\text{Hit Rate} = \frac{\text{Number of hits}}{\text{Number of accesses}}$$

$$\text{Miss Rate} = \frac{\text{Number of misses}}{\text{Number of accesses}}$$

$$\text{Hit Rate} + \text{Miss Rate} = 1$$

The expected access time E_L for a memory level L with latency t_L and miss rate M_L :

$$E_L = t_L + M_L \cdot E_{L+1}$$



Memory Performance Example

Two-level hierarchy: Cache and main memory

Program executes 1000 loads & stores

750 of these are found in the cache

What's the cache hit and miss rate?

Memory Performance Example

Two-level hierarchy: Cache and main memory

Program executes 1000 loads & stores

750 of these are found in the cache

What's the cache hit and miss rate?

$$\text{Hit Rate} = \frac{750}{1000} = 75\%$$

$$\text{Miss Rate} = 1 - 0.75 = 25\%$$

If the cache takes 1 cycle and the main memory 100,

What's the expected access time?

Memory Performance Example

Two-level hierarchy: Cache and main memory

Program executes 1000 loads & stores

750 of these are found in the cache

What's the cache hit and miss rate?

$$\text{Hit Rate} = \frac{750}{1000} = 75\%$$

$$\text{Miss Rate} = 1 - 0.75 = 25\%$$

If the cache takes 1 cycle and the main memory 100,

What's the expected access time?


Expected access time of main memory: $E_1 = 100$ cycles

Access time for the cache: $t_0 = 1$ cycle

Cache miss rate: $M_0 = 0.25$

$$E_0 = t_0 + M_0 \cdot E_1 = 1 + 0.25 \cdot 100 = 26 \text{ cycles}$$


A Direct-Mapped Cache



This simple cache has


- ▶ 8 sets
- ▶ 1 block per set
- ▶ 4 bytes per block

To simplify answering “is this data in the cache?,” each byte is mapped to exactly one set.



2^3 -Word Cache

Direct-Mapped Cache Hardware



Address bits:

0–1: byte within block

2–4: set number

5–31: block “tag”

Cache hit if
in the set of the address,

- ▶ block is valid ($V=1$)
- ▶ tag (address bits 5–31) matches

Direct-Mapped Cache Behavior

A dumb loop:


repeat 5 times

load from 0x4;

load from 0xC;

load from 0x8.

```
li    $t0, 5
l1:  beq    $t0, $0, done
     lw     $t1, 0x4($0)
     lw     $t2, 0xC($0)
     lw     $t3, 0x8($0)
     addiu  $t0, $t0, -1
     j     l1
done:
```



Assuming the cache starts empty, what's the miss rate?

Direct-Mapped Cache Behavior

A dumb loop:


repeat 5 times

load from 0x4;

load from 0xC;

load from 0x8.

```
li    $t0, 5
l1:  beq    $t0, $0, done
      lw    $t1, 0x4($0)
      lw    $t2, 0xC($0)
      lw    $t3, 0x8($0)
      addiu $t0, $t0, -1
      j     l1
done:
```



Assuming the cache starts empty, what's the miss rate?


4	C	8	4	C	8	4	C	8	4	C	8	4	C	8
M	M	M	H	H	H	H	H	H	H	H	H	H	H	H

$3/15 = 0.2 = 20\%$

Direct-Mapped Cache: Conflict

A dumber loop:
repeat 5 times
load from 0x4;
load from 0x24

```
li    $t0, 5
l1:  beq  $t0, $0, done
     lw   $t1, 0x4($0)
     lw   $t2, 0x24($0)
     addiu $t0, $t0, -1
     j    l1
done:
```




Assuming the cache starts empty,
what's the miss rate?

These are *conflict misses*

Direct-Mapped Cache: Conflict

A dumber loop:
repeat 5 times
load from 0x4;
load from 0x24

```
li    $t0, 5  
l1:  beq    $t0, $0, done  
     lw     $t1, 0x4($0)  
     lw     $t2, 0x24($0)  
     addiu  $t0, $t0, -1  
     j     l1  
done:
```




Assuming the cache starts empty, what's the miss rate?

$$\frac{4 \ 24 \ 4 \ 24 \ 4 \ 24 \ 4 \ 24 \ 4 \ 24}{M \ M \ M \ M \ M \ M \ M \ M \ M \ M}$$

10/10 = 1 = 100% Oops

These are *conflict misses*

No Way! Yes Way! 2-Way Set Associative Cache



2-Way Set Associative Behavior

```

li    $t0, 5
l1:  beq  $t0, $0, done
      lw   $t1, 0x4($0)
      lw   $t2, 0x24($0)
      addiu $t0, $t0, -1
      j    l1
done:

```

Assuming the cache starts empty, what's the miss rate?


4	24	4	24	4	24	4	24	4	24
M	M	H	H	H	H	H	H	H	H

$2/10 = 0.2 = 20\%$

Associativity reduces conflict misses

Way 1			Way 0			
V	Tag	Data	V	Tag	Data	
0			0			Set 3
0			0			Set 2
1	00...00	mem[0x00...24]	1	00...10	mem[0x00...04]	Set 1
0			0			Set 0

An Eight-way Fully Associative Cache





No conflict misses: only compulsory or capacity misses

Either very expensive or slow because of all the associativity

Exploiting Spatial Locality: Larger Blocks

0x8000 0009C:

Memory
Address





2 sets

1 block per set (Direct Mapped)

4 words per block

Direct-Mapped Cache Behavior w/ 4-word block





Cache when reading 0xC

The dumb loop:
repeat 5 times
load from 0x4;
load from 0xC;
load from 0x8.

```
li    $t0, 5
l1:  beq    $t0, $0, done
     lw     $t1, 0x4($0)
     lw     $t2, 0xC($0)
     lw     $t3, 0x8($0)
     addiu  $t0, $t0, -1
     j     l1
done:
```

Assuming the cache starts empty, what's the miss rate?

Direct-Mapped Cache Behavior w/ 4-word block



The dumb loop:

repeat 5 times

load from 0x4;

load from 0xC;

load from 0x8.

Cache when reading 0xC

```

li    $t0, 5
l1:  beq    $t0, $0, done
     lw     $t1, 0x4($0)
     lw     $t2, 0xC($0)
     lw     $t3, 0x8($0)
     addiu $t0, $t0, -1
     j     l1
done:

```

Assuming the cache starts empty, what's the miss rate?


4 C 8 4 C 8 4 C 8 4 C 8 4 C 8

M H H H H H H H H H H H H H H H

$1/15 = 0.0666 = 6.7\%$

Larger blocks reduce compulsory misses by exploiting spatial locality

Stephen's Desktop Machine Revisited











AMD Phenom
9600
Quad-core
2.3 GHz
1.1–1.25 V
95 W
65 nm

On-chip caches:

Cache	Size	Sets	Ways	Block
L1I*	64 K	512	2-way	64-byte
L1D*	64 K	512	2-way	64-byte
L2*	512 K	512	16-way	64-byte
L3	2 MB	1024	32-way	64-byte

* per core

Intel On-Chip Caches

	Chip	Year	Freq. (MHz)	L1		L2
				Data	Instr	
	80386	1985	16–25	off-chip		none
	80486	1989	25–100	8K unified		off-chip
	Pentium	1993	60–300	8K	8K	off-chip
	Pentium Pro	1995	150–200	8K	8K	256K–1M (MCM)
	Pentium II	1997	233–450	16K	16K	256K–512K (Cartridge)
	Pentium III	1999	450–1400	16K	16K	256K–512K
	Pentium 4	2001	1400–3730	8–16K	12k op trace cache	256K–2M
	Pentium M	2003	900–2130	32K	32K	1M–2M
	Core 2 Duo	2005	1500–3000	32K per core	32K per core	2M–6M _{23/1}