COMS W3101 Programming Language: C++ (Fall 2014)

Ramana Isukapalli ramana@cs.columbia.edu

Lecture-2

Overview of C ... continued

- Functions
- Structures
- Pointers
- C++
 - Design, difference with C
 - Concepts of Object oriented Programming
 - Concept of class and Object
 - Constructor and destructor
 - Data and Member functions
 - Data encapsulation
 - public, private and protected members

C functions

- A group of statements
 - To perform a task
 - Possibly return a value

C functions ... example

Example

```
int square (int x) /* fn to compute square*/
  return (x * x);
void main()
               /* Starting point of ANY C program*/
  int i = 5;
  int i_sq = square (5);
  printf ("Square of 5 is: %d\n", i_sq);
```

C structs

C struct

- used to contain > 1 basic data types
- Can contain other structs
- E.g., typedef struct { int a, b, c; float x,y,z; } myStruct;

```
myStruct m;
m.a = 1;
```

C pointers

- A pointer "points" to a memory location.
 - E.g., int x; /* x is an integer */ int *y; /* y points to an integer */ x = 5;

y = 6; / NOT y = 6 ! */

- Pointers can point to any data type;
 - int *x; short *y; char *str;
 - double *z; void *p, etc.

C pointers, contd.

- Why do we need pointers?
 - Mainly to manage the memory, as opposed to the compiler managing memory.
 - User needs to assign and delete memory.
 - Allocate memory using malloc.
 - Delete memory using free.
- Examples
 - int *x = (int *) malloc (sizeof (int));
 *x = 3;
 - free (x);



-

C++ — Philosophically different from C

- High level features of C++
 - Uses concepts of "object oriented programming" (OOP)
 - Everything that works in C works in C++
 - C syntax, operators, structures, control statements, etc. work in C++
 - Reverse is NOT true
- Object Oriented Programming
 - Concept of class/object, methods, inheritance, encapsulation, abstraction, polymorphism
 - Key concepts in this
 - Separation of data and methods

Class methods

Syntax:

```
<ret_type> class::functionName(args)
{
    // code
}
```

Method code can be present in class definition

- Outside the class definition
- In a separate file

Example

```
void account::withdrawMoney (int amount)
{
    // code
    W3101: Programming Languages: C++
    Ramana Isukapalli
```

A simple "account" example

class account private: int user_SSN; // data int accountNumber; // data public: void withdrawMoney (int amount); // method void depositMoney (int amount); // method: void computeInterest(); // method }; account x; // x is an object of class "account" Ramana Isukapalli

Ramana Isukapalli W3101: Programming Languages – C++ Constructor and Destructor

Constructor and destructor ... contd.

Constructor

- o A function with the same name as the class
- o Called when an object is created
- o A class can have more than one constructor

Destructor

- o Called when an object is cleaned up (goes out of scope)
- o One class can have only one destructor

Examples

account x; // constructor code is called account *y = new account; // constructor code is called delete (y); // destructor code is called

Constructor and destructor

Constructor code

```
account::account()
  { user_ssn = -1; accountNumber = -1; }
  account::account(): user_ssn(-1),
                         accountNumber(-1) { }
  account::account (int ssn, int acctNum)
  ł
      user_ssn = ssn;
      accountNumber = acctNum:
  }
Destructor code
  account::~account()
  { // Any memory/resource cleanup, etc. }
```

Initializing member values

```
class Account
{
    private:
    int balance;
    public:
        Account (): balance (0)
        {}
        Account (int amount):
        balance (amount) {}
};
```

```
class checkingAccount : public
    Account
{
    checkingAccount (int amount)
    : Account (amount) { }
}
```