

COMS W4115

Programming Languages and Translators

Homework Assignment 2

Prof. Stephen A. Edwards Due December 1st, 2005
Columbia University at 11:00 AM (beginning of class)

Submit solution on paper (no email). Please write your name clearly on the paper.

Do this assignment alone. You may consult the instructor and the TAs, but not other students.

1. Consider the following Prolog program.

```
takes(jane_doe, his201).
takes(jane_doe, cs254).
takes(ajit_chandra, art302).
takes(ajit_chandra, cs254).
classmates(X,Y) :- takes(X,Z), takes(Y,Z).
```

What does the query `classmates(jane_doe,X)` return? Give details of how the search procedure produces this result.

2. Consider the following C-like program.

```
int w = 3;
int x = 10;

int incw() { return ++w; }
int incx() { return ++x; }

void foo(y, z){
    printf("%d\n", y + y);
    x = 1;
    printf("%d\n", z);
}

int main() {
    foo(incw(), incx());
    return 0;
}
```

What does it print if the language uses

- (a) Applicative-order evaluation?
- (b) Normal-order evaluation?

3. In an assembly-language-like notation (e.g., use MIPS or a pseudocode of your own choosing), write what a good optimizing compiler would produce for the following two switch statements:

```
switch (a) {
case 1: x = 3; break;
case 2: x = 5; break;
case 3: x = 15; break;
case 4: x = 20; break;
case 5: x = 23; break;
default: x = 28; break;
}
```

```
switch (b) {
case 1: x = 3; break;
case 10: x = 5; break;
case 100: x = 15; break;
case 1000: x = 20; break;
default: x = 25; break;
}
```

4. For a 32-bit little-endian processor with the usual alignment rules, show the memory layout and size in bytes of the following C types.

```
union {
    struct {
        int a; /* 32-bit */
        char b; /* 8-bit */
    } s;
    int c;
} ul;
```

```
struct {
    char a;
    short b;
    int c;
    char d;
} sl;
```

```
struct {
    char a;
    char d;
    short b;
    int c;
} s2;
```