Genesis

And on the first day...

Samuel Cohen (slc2206) - Manager Michael Wang (mlw2167) - Language Guru Leon Stilwell (ls3223) - Language Guru Jason Zhao (jsz2107) - Systems Architect Saahil Jain (sj2675) - Tester

<u>Introduction</u>

Genesis is a Java-like language that allows for the easy creation of 2D games.

This language utilizes a collision operator to abstract away the logic behind collision detection so that the programmer can focus on the game mechanics.

It also include a complex data type "cluster" that serves as the fundamental building block for game design.

Data Types:

Primitive data types (Passed by value)

- int
- float
- char
- boolean

Туре	Description
int	integer Example: 100
float	float Example: 2.3
char	character Example: 'a'
boolean	Boolean value (true or false) example: true

Complex data types(Passed by reference)

Туре	Description
pixel	X value, Y value, color Example:
color	R value, G value, B value
cluster	 Collection of points and/or previously defined clusters which form a geometric shape and it's accompanying color. Includes an anchor point to reference the shape.
array	A container that holds data, dynamically sized

Language Components:

Control Flow

- if
- elif
- else
- while
- for

Game Specific

• START - creates and displays a gameboard with provided dimensions, pixel size, and background color.

Indexing

- Indexing starts at 0
- Subarrays are indexed by brackets [] with a : separating first and second indices similar to Python. The first index is inclusive, and the second index is exclusive. For example array[1:5] includes the element at index 1 until but not including the element at index 5.

Function

• func returnType funcName(args) { }

Comments

• Comment Symbol: //

Logical Operators

- AND
- OR
- NOT

Comparison Operators

- Equals: ==
- Not equals: !=
- Greater than or equals: >=
- Less than or equals: <=
- Greater than: >
- Less than: <

Math Operators

- Multiply: *
- Divide: /
- Add: +
- Subtract: -
- Modulo: %

Collision-to-event Operator

• clust1 <!> clust2 returns whether clusters clust1 and clust2 are currently touching (in adjacent pixels) or overlapped

User Input


- keyPressed(KEYNAME) returns whether KEYNAME is pressed
- keyReleased(KEYNAME) returns whether KEYNAME was released since the last frame

Time & Clock Speed

- Timing is controlled by providing deltaTime, the time that has elapsed since the last frame was rendered, through the onUpdate function.
- The engine will render frames as quickly as possible (Clock speed is not defined by the programmer or the language)

Code Example

- In the background grab the screen resolution/dimensions and scale appropriately
- Initialize dimensions n * m
- Initialize square pixel size x * x
- Initialize background color <r,g,b> (Prim)
- Define timer: paired with seconds on a clock
- User inputs (keys &/or mouse)
- Define shapes/color



```
cluster player = new cluster{
      //These properties are of type int
      x=200;
      y=480;
      width=100;
      height=100;
      color = <0, 0, 255>;
      // Automatically gets called by engine
      onUpdate(float deltaTime) {
            if(keyPressed("right")) {
                  timePressed += deltaTime;
                  if(timePressed > .1){
                        //Move if the key has been pressed for .1 sec
                        this.x += 1;
                        timePressed = 0;
                  }
            } else {
                  timePressed = 0;
            }
            //Check for collision
            if(this<!>lavaWall){
                  this.delete();
            }
      }
}
//Global update function
onUpdate(float deltaTime){
      if(keyPressed("esc")){
            wall.delete();
            player.delete();
      }
}
```